DECLARATION OF PERFORMANCE

Dop 067 - Rev 02.2021

- 1. Unique identification code of the product-type: IAMSUB AIRLESS
- 2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): **see packaging**
- 3. Intended use of uses of the production product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer (annex ZA, table ZA.1 of the relevant specification) :
 - EN 1504-2:2004 product and systems for the protection and repair of concrete structures
- 4. Name, registered trade name or registered trade mark and contact address of the manufacture as required pursuant in Article 11(5): Colorificio Zetagi Srl Via Pasubio, 41 IT 36051 CREAZZO (VI)
- 5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(3):
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
 - EN 1504-2:2004 AVCP System 2+
- 7. In case of declaration of performance concerning a construction product covered by a harmonized standard
 - NBN EN 1504-2:2004 : Belgian Construction Certification Association npo, identified as Notified FPC Certification Body under registration #0749 performed certification of constancy of performance of the product under AVCP System 2+, on the basis of the following items:
 - a) The manufacturer carries out:
 - i. Factory Production Control
 - ii. Determination of the product type
 - b) The Notified FPC Certification Body issues the EC-certificate of conformity of the Factory Production Control on the basis of:
 - i. Initial inspection of the manufacturing plant and of the Factory Production Control
 - ii. Continuous surveillance, assessment and approval of the Factory Production Control
- 8. In case of declaration of performance concerning a construction product for which a European Technical Assessment has been issued : **Not applicable**

9. Declared performance

Essential requirements	Units	Performances	Harmonised technical specifications
Compressive strength	[N/mm²]	NPD	
Capillary absorption and permeability to water	[kg/(m².h ^{0,5})]	NPD	
Linear shrinkage	%>		
		NPD	
Resistance to thermal shock	[N/mm²]	NPD	EN 1504-2:2004
Resistance to severe chemical attack	-	NPD	
Crack bridging ability	-	NPD	
Abrasion resistance		NPD	
Adhesion strength by pull of test	[N/mm ²]	≥2	
Reaction to fire	-	NPD	
CO2 permeability		NPD	
Artificial weathering	-	NPD	
Antistatic behaviour	[Ω]	NPD	
Adhesion on wet concrete	-	NPD	
Dangerous substances	-	See SMDS	

Creazzo, 05.06.2021

Lorenzo Bertazzo